

Product Specifications

Item #GP102



**Magid® ROC® GP102 Sustainable Lightweight Foam
Nitrile Palm Coated Work Glove**

PRODUCT DESCRIPTION	
Product Classification	General Purpose Work Glove – Coated
Construction/Design	15-gauge, seamless machine knit
Composition	Recycled polyester and spandex blend shell with foam nitrile palm coating
Color(s)	Grey shell; black palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: light blue (5), navy blue (6), purple (7), green (8), brown (9), yellow (10), grey (11), white (12)
Unit of Measure	Dozen
Packaging	12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Soft, flexible, and sustainably manufactured foam nitrile coating ensures great grip of small parts even in wet/oily conditions • 90% recycled polyester (contains an average of 66% post-consumer recycled content) and 10% spandex blend • Dark color hides dirt and grime to extend wear • Silicone-free, low-lint construction minimizes product contamination • Color-coded overcast for easy sorting and dispensing • Rubber band edge reduces fraying • Industry-leading pricing • Packaged in 100% recycled materials • ANSI Level A1 Cut Resistance, ANSI Level 4 Abrasion Resistance • Secured Environmental Claim Validation (ECVP) for Recycled Content, UL 2809-2, Edition 2.1	

APPLICATIONS	
Assembly, shipping and receiving, material handling and general maintenance.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GP1025	GP1026	GP1027	GP1028	GP1029	GP10210	GP10211	GP10212

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A1
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water, and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).		

Originator	Kim Schultz	Date	04/25/2023	
Revised By	Kim Schultz	Date	06/12/2026	Revision # 8

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

