

Product Specifications

Item #GP150



Magid® ROC® Lightweight Polyurethane Palm Coated Work Glove

PRODUCT DESCRIPTION							
Product Classification	General Purpose Work Glove – Coated						
Construction/Design	15-gauge, seamless machine knit						
Composition	100% nylon shell, polyurethane palm coating						
Color(s)	Grey shell, grey palm coating						
Size(s)	5 - 11						
Cuff/Finish	Color-coded overcast: yellow (5), white (6), green (9), yellow (10), grey (11)						
Unit of Measure	Dozen						
Packaging	Dozen per inner pack, 20 inner packs per case						
FEATURES & BENEFITS							
• 15-gauge nylon shell offers superior breathability and comfort • Polyurethane palm coating channels away oils and ensures a secure grip • Silicone-free, low-lint construction minimizes product contamination • Color-coded overcast reduces fraying and acts as a visual aid for sizing • Industry-leading pricing makes for an excellent value • PPG Tested • ANSI Cut Level 1 Cut Resistance and ANSI Level 4 Abrasion Resistance							
APPLICATIONS							
Assembly, shipping and receiving, material handling and general maintenance.							
AVAILABLE STYLES							
Size	5	6	7	8	9	10	11
Part Number	GP1505	GP1506	GP1507	GP1508	GP1509	GP15010	GP15011

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	1
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Sarah Anderson	Date	09/04/2013	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.