

Product Specifications

Item #GPD534



D-ROC®
by Magid

**Magid® D-ROC® Polyurethane Palm Coated Work
Glove – Cut Level A4**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	10-gauge, seamless machine knit
Composition	Hyperon® shell; polyurethane palm coating
Color(s)	Salt & pepper shell; grey palm coating
Size(s)	6 – 11
Cuff/Finish	Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case
FEATURES & BENEFITS	
• Cool and breathable Hyperon® fiber blended shell delivers comfort, dexterity and 360° cut protection • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Color-coded overcast acts as a visual aid for sizing • Elasticized finish on cuff reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A4 Cut Resistance under the ANSI/ISEA 105-2016 standard, ANSI Level 6 Abrasion Resistance and ANSI Level 3 Puncture Resistance • Rated an ANSI Cut Level 4 under the ANSI/ISEA 105-2011 standard using the ASTM F-1790-97 test method	
APPLICATIONS	
Assembly, machining, automotive manufacturing, metal handling, maintenance and construction	

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	A4
Abrasion Resistance	-	6
Puncture Resistance	6.4	3
European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks		
Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Sarah Anderson	Date	05/09/2014	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	GPD5346	GPD5347	GPD5348	GPD5349	GPD53410	GPD53411

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

