

Product Specifications

Style #GPD682



D-ROC®

Magid® D-ROC® AeroDex® 18-Gauge Extremely Lightweight Polyurethane Coated Work Glove – ANSI Cut Level A6

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	18-gauge, seamless machine knit
Composition	AeroDex® shell; polyurethane palm coating
Color(s)	Blue shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• AeroDex® engineered yarn delivers extremely lightweight A6 cut resistance that is 50% lighter than a traditional HPPE of the same cut level • 18-gauge AeroDex® shell delivers unmatched dexterity & tactile sensitivity making it agile enough for any job even those that require a high level of cut protection • AeroDex® is specially engineered to make your hands feel cooler than a comparable cut resistant glove • Lightweight polyurethane palm coating maintains dexterity while delivering excellent grip • Touchscreen compatible to maintain user safety while operating electronic devices • Nitrile reinforced thumb saddle enhances durability at a critical wear point • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Machine washable for longer service life • ANSI Level A6 Cut Resistance, ANSI Level 5 Abrasion Resistance, ANSI Level 3 Puncture Resistance	

APPLICATIONS								
Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, assembly, and paper production.								
AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD6825	GPD6826	GPD6827	GPD6828	GPD6829	GPD68210	GPD68211	GPD68212
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria								
Test Method						Clause	ANSI Level	
ASTM F2992 Cut Resistance						-	A6	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)						-	5	
ANSI/ISEA: 105 Puncture Resistance						6.4	3	
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects		Holes/tears						
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	5/27/2020		
Revised By	Kim Schultz	Date	5/8/2024	Revision #	3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.