

Product Specifications

Style #GPD787



D-ROC®

**Magid® D-ROC® AeroDex® Lightweight 13-Gauge
RepTek Grip® Silicone Palm Coated Work Glove –
Cut Level A7**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	AeroDex® shell; RepTek Grip® silicone palm coating
Color(s)	Blue shell; clear palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), white (11), orange (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• 13-gauge AeroDex® engineered shell delivers extremely lightweight A7 cut resistance that is 50% lighter than a traditional HPPE of the same cut level • AeroDex® is specially engineered to make your hands feel cooler than a comparable cut resistant glove • Durable clear silicone palm coating provides unmatched dry grip even on heavy objects • Silicone coating delivers adhesion resistance, preventing sealant and hot melt build up • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A7 Cut Resistance, ANSI Level 6 Abrasion Resistance, ANSI Level 3 Puncture Resistance	

APPLICATIONS	
Window and door fabrication, hot melt and sealant work, appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, assembly	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD7875	GPD7876	GPD7877	GPD7878	GPD7879	GPD78710	GPD78711	GPD78712
FUNCTIONAL PERFORMANCE								
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria								
Test Method						Clause	ANSI Level	
ASTM F2992-15 Cut Resistance						-	A7	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)						-	6	
ANSI/ISEA: 105-2011 Puncture Resistance						6.4	3	
SERVICE LIFE								
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.								
Critical Defects		Holes/tears						
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES								
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.								
GENERAL INFORMATION								
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.								

Originator	Scott Daigle	Date	3/10/2020		
Revised By	Dana Cornish	Date	02/25/2022	Revision #	3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD

1300 Naperville Drive | Romeoville, IL 60446
800-444-8030 | magidglove.com

Page 2 of 2

