

Product Specifications

Item #GPD820



D-ROC®
by Magid

Magid® D-ROC® GPD820 Lightweight NitriX® Palm Coated Work Gloves – Cut Level A6

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit shell
Composition	Hyperon™ shell; NitriX® palm coating
Color(s)	Dark grey shell, black coating
Size(s)	5 – 11
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	PR
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• 13- gauge Hyperon™ shell delivers a ground-breaking combination of ultra-lightweight comfort and maximum 360° cut protection • NitriX® Grip Technology palm coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increases wear life • Touchscreen compatible • Dark grey color hides dirt and grime to extend wear • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • PPG and NEAT Tested • Machine washable for longer service life • 360° ANSI Cut Level A6 protection, ANSI Level 5 Abrasion Resistance and ANSI Level 5 Puncture Resistance	

APPLICATIONS

Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling and Metal Stamping

AVAILABLE STYLES

Size	5	6	7	8	9	10	11
Item Number	GPD8205	GPD8206	GPD8207	GPD8208	GPD8209	GPD82010	GPD82011

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
EN 388:2003 Puncture Resistance	-	5

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	5

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

Originator	Sarah Anderson
-------------------	----------------

Revised By	Olivia DeVries
-------------------	----------------

Date	11/20/2015
-------------	------------

Date	06/01/2022	Revision #	2
-------------	------------	-------------------	---

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.