

Product Specifications

Style #PCT455



D-ROC®
by Magid

Magid® D-ROC® Black Hornet™ PCT455 18-Gauge 3-Layer HPPE and Steel Blend Crinkle Latex Coated Work Glove – Cut Level A9

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Needle Stick Puncture Resistant, Coated
Construction/Design	18-gauge, 3-layer seamless machine knit shell, puncture-resistant liner
Composition	Hyperon® shell; 3/4 crinkle latex palm coating
Color(s)	Grey shell; black palm coating
Size(s)	6 – 11
Cuff/Finish	Color-coded elasticized overcast: grey (6), blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• 18-gauge Hyperon® shell delivers dexterity, breathability, and comfort • Crinkle latex palm coating delivers superior abrasion resistance and dry grip • Puncture-resistant liner on the palm and fingers offers protection from needlesticks and other sharp objects • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • ANSI Level A9 Cut Resistance, ANSI F2878 Level 5 Hypodermic Needle Puncture Resistance	

APPLICATIONS	
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	PCT4556	PCT4557	PCT4558	PCT4559	PCT45510	PCT45511

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A9
ASTM F2878 Hypodermic Needle	-	5
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Dana Cornish	Date	8/30/2021	
Revised By	Dana Cornish	Date	9/21/2021	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.