

Product Specifications

Item #TRX526W



T-REX™
by Magid

Magid® T-REX® Arctic Series® 15-Gauge Merino Wool Lined, Low-Profile Impact 1 Winter Work Gloves

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Wool lined, Coated
Construction/Design	15-gauge, insulated seamless machine knit shell, 7-gauge fleece liner; impact protection on back of hand and fingers; reinforced thumb saddle.
Composition	Hyperon® shell; merino wool liner; foam nitrile palm coating; HPT water-repellent full coating
Color(s)	Black shell; black palm coating, red/black/white TPR
Size(s)	S - XXXL
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 72 pairs per case

FEATURES & BENEFITS	
15-gauge Hyperon® shell delivers breathability, comfort and cut protection - Merino wool lining defends against cold temperatures and provides moisture-wicking warmth without scratchiness or irritation - HPT water-repellent finish is safe to launder, staying effective for the life of the glove - Foam nitrile palm provides added wet and dry grip - M-Force Defense System™ back-of-hand protection extends all the way to the fingertips and between thumb and index finger to deflect and absorb impacts - Reinforced thumb saddle enhances durability at a critical wear point - Black color hides dirt, extends worker wear time - Touchscreen compatible to maintain user safety while operating electronic devices - ANSI Level A5 Cut Resistance, ANSI Level 5 Abrasion Resistance, ANSI Level 4 Puncture Resistance - ANSI/ISEA 138 Impact Level 1 (Level 1 protection on knuckles and Level 1 protection on fingers)	

APPLICATIONS	
Construction, waste removal, transportation, and cold storage applications.	

AVAILABLE STYLES						
Size	S	M	L	XL	XXL	XXXL
Item Number	TRX526WS	TRX526WM	TRX526WL	TRX526WXL	TRX526WXXL	TRX526WXXXL

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)		5
ANSI/ISEA: 105 Puncture Resistance	6.4	4
US Standard: ANSI/ISEA 138 American National Standard for Performance and Classification for Impact-Resistant Gloves		
Test Method	Clause	ANSI Level
ISEA 138:201x Impact Protection (Overall)	-	1
ISEA 138:201x Impact Protection (Knuckles)	-	1
ISEA 138:201x Impact Protection (Fingers and Thumb)	-	1
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).		

Originator	Kim Schultz	Date	08/27/2024	
Revised By	Kim Schultz	Date	12/12/2024	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

