

Product Specifications

Item #TRX543W



T-REX™
by Magid

**Magid® T-REX® Arctic Series® Thermal Impact Glove –
Cut Level A5**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Impact
Construction/Design	15-gauge seamless machine knit shell; 7-gauge fleece liner; impact protection on back of hand and fingers
Composition	DuraBlend™ shell; Insulcore® Extreme Thermal Lining; thermoplastic rubber (TPR) pads on the back of the hand and fingers; foam nitrile palm coating; aramid reinforced thumb saddle
Color(s)	Salt & pepper shell; black palm; blue, grey & white TPR
Size(s)	S-3XL
Cuff/Finish	Knit cuff with color-coded elasticized overcast: light blue (S), green (M), red (L), black (XL), orange (2XL), white (3XL)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 48 pairs per case

FEATURES & BENEFITS

- Insulcore® Extreme Thermal Lining delivers ultimate protection against cold temperatures
- DuraBlend™ machine knit shell delivers comfort, dexterity and 360° cut protection
- M-Force Defense System™ back-of-hand protection extends all the way to the fingertips and between thumb and index finger to deflect and absorb impacts
- Flexible foam nitrile palm coating channels oil away for a superb grip in light oil applications
- Reinforced aramid thumb saddle strengthens critical wear point
- Color-coded overcast acts as a visual aid for sizing and helps prevent fraying
- ANSI Level A5 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 5 Puncture Resistance
- ANSI/ISEA 138 Impact Level 2 (Level 2 protection on knuckles and Level 2 protection on fingers)

APPLICATIONS

Oil & gas drilling, extraction, fracking, refining, mining, demolition, heavy construction, material handling

AVAILABLE STYLES						
Size	S	M	L	XL	2XL	3XL
Item Number	TRX543WS	TRX543WM	TRX543WL	TRX543WXL	TRX543WXXL	TRX543WXXXL
FUNCTIONAL PERFORMANCE						
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria						
Test Method				Clause	ANSI Level	
ASTM F-1790-97 Cut Resistant				-	A5	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 500 gram load)				-	4	
EN 388:2003 Puncture Resistance				6.4	5	
US Standard: ANSI/ISEA 138 American National Standard for Performance and Classification for Impact-Resistant Gloves						
Test Method				Clause	ANSI Level	
ISEA 138:201x Impact Protection (Overall)				-	2	
ISEA 138:201x Impact Protection (Knuckles)				-	2	
ISEA 138:201x Impact Protection (Fingers and Thumb)				-	2	
SERVICE LIFE						
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.						
Critical Defects		Holes/tears				
Major Defects		Dimensional or weight nonconformance, discoloration, other fabric defects				
LAUNDERING GUIDELINES						
Machine wash in cold water and air dry. Do not bleach. Do not machine dry. Do not iron.						

Originator	Scott Daigle	Date	6/26/2019			
Revised By	Kim Schultz	Date	11/17/2023	Revision #	2	

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.