

Product Specifications

Item # TRX858OB

ANSI/ISEA 105



T-REX®
by Magid

Magid® T-REX® Inferno Series® Oil Blocking Cow Grain Welder's FR Impact Glove – Cut Level A5

PRODUCT DESCRIPTION

Product Classification	Leather Impact Welding Gloves – Cut Resistant
Construction/Design	Cut and sewn, Gunn cut pattern, keystone thumb, shirred elastic at wrist, impact protection on back of hand and fingers
Composition	Cow grain leather shell with oil block technology; aramid blend knit fabric liner, flame resistant thermoplastic rubber (TPR) pads on the back of the hand, fingers, and fingertips
Color(s)	Brown leather; black and orange TPR pads
Cuff/Finish	3.5" grain leather gauntlet cuff
Size(s)	S-4XL
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 48 pairs per case

FEATURES & BENEFITS

- Flame Resistant M-Force Defense System™ back-of-hand protection deflects and absorbs impacts while delivering protection from heat and open flame up 750°F
- Premium cow grain leather shell provides dexterity and abrasion resistance
- Oil blocking technology repels water and oil
- Stitched-in para-aramid blend knit fabric liner delivers an optimal fit and dependable cut protection
- Para-aramid stitching maintains heat & flame resistance and strengthens the glove
- Fully lined 3 ½" Gauntlet Cuff extends protection past your hands
- Gunn cut pattern increases comfort and dexterity
- ANSI Level A5 Cut Resistance, ANSI Level 4 Abrasion Resistance, and ANSI Level 4 Puncture Resistance
- ANSI/ISEA 138 Impact Level 1 (Level 1 protection on knuckles and Level 1 protection on fingers)
- EN 407 Limited Flame Spread Level 3

APPLICATIONS

Welding, brazing, Oil & gas rigging and refining, utilities, manufacturing, heavy construction, demolition, agriculture, emergency response, military, mining, steelwork, ironwork, automotive, metal stamping, glass handling.

AVAILABLE STYLES							
Size	S	M	L	XL	XXL	XXXL	XXXXL
Item #	TRX858OBS	TRX858OBM	TRX858OBL	TRX858OBXL	TRX858OBXXL	TRX858OBXXXL	TRX858OBXXXXL

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A5
ASTM D3389 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388 Puncture Resistance (other than hypodermic needle)	6.4	4

US Standard: ANSI/ISEA 138 American National Standard for Performance and Classification for Impact-Resistant Gloves		
Test Method	Clause	ANSI Level
ISEA 138:201x Impact Protection (Overall)	-	1

European Standard: EN 407 Protection Against Thermal Risks (Heat and/or Fire)		
Test Method	Clause	EN Level
EN 407 Limited Flame Spread	5.1	Pass/Level 3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

For best results, leather gloves should be dry-cleaned only.

Originator	Scott Daigle	Date	01/9/2023	
Revised By	Kim Schultz	Date	05/05/2026	Revision # 7

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.